





Verticalle

It's Your View Enjoy it with Westbury VertiCable® (Style C80)

VertiCable® offers contemporary vertical cables and balusters providing an architectural style and virtually unobstructed views. All sections are factory assembled, tensioned, and shipped on pallets ready for quick installation. VertiCable® hardware mirrors Westbury® C-Series products allowing consistent design, performance, and configuration for the contractor or builder. VertiCable® is available in 12 standard AAMA 2604 compliant powder coated colors. Custom AAMA 2604 colors are available as special order. AAMA 2605 colors are all special order.







VERTICABLE® SPECIFICATIONS

- Section Heights: 36", 42"
- Section Lengths: 4', 5', 6', 7', 8'
 (7' & 8' in 36" height only)
- · Stair Rail Lengths: 4', 5', 6'
- · C80 Baluster: 5/8" round
- Cable Spacing: 3" c/c
- Stylish Top Rail: 1-3/4" w (.090") x 1-3/8" t (.085")
- Bottom Rail: 1-3/4" w (.080") x 1-1/4" t (.080")
- 1/8" Stainless Steel Cable with Fasteners
- Bottom Rail Support: 7', 8'
- Stair Sections Rack 30° 40° with Standard Stair Mounts (included)
- Straight Sections Rack 1° 10° with Stair Swivel Mounts (not included)
- Stair Sections Rack 20° 40° with Stair Swivel Mounts (not included)



VertiCable® Gates in 36", 48", and 60" widths. 36" x 36" Gate shown above



VertiCable® with Level Crossover Post Offers a Contemporary and Streamlined Look. Works well with Westbury® Drink Rail. Color: Bronze Fine Texture

Exclusive DSI Powder Coating Process

AAMA 2604 & AAMA 2605





Verified AAMA 2604 **Compliant Powder Coating**

Westbury® Aluminum Railing powder coating is an uncompromising quality created by state-of-the-art technology. This is the highest quality powder coating on the market with a lifetime-limited warranty giving you peace of mind in your investment.



The raw premium-grade aluminum is inspected to be free of blemishes and is not exposed to the outdoor elements.



The product enters a heated acidic cleaning stage to remove extrusion debris and fabrication oils.



CLEAN: City water rinse CLEANER: Recycling reverse osmosis

CLEANEST: Pure reverse osmosis water rinse SEALER: Dried-in-place aluminum sealer



A 200 MPH air blast removes water drops from the pre-treated aluminum. A convection oven completes the dry-off process.



Powder is applied with 18 automated and 2 manual spray guns. Compressed process air is dried to -35°F Dew Point for superior adhesion.



adhered to the aluminum sub-straight in a 400 degree cure stage.







Available Standard Colors

Black Fine Texture



Ninety Bronze



Bronze Fine Texture



Gloss White




White Fine Texture



Brown Fine Texture



Speckled Walnut



Sandy Shore







DSI is a PCI 4000 certified and verified AAMA 2604 and AAMA 2605 compliant powder coating applicator. The powder coating process is accredited by the American Architectural Manufacturing Association and the Powder Coating Institute. Our powder coating is custom blended from a Super Durable Polyester TGIC (Triglycidyl Isocyanurate) resin-base, using premium pigmentation to meet AAMA 2604 specifications. Our AAMA 2605 is a fluorocarbon polymer resin system.

Silver

VertiCable® Accessories

Westbury® Accessories add the finishing touch to your masterpiece. A variety of post sizes and wall thicknesses add strength to your railing. The combination of mounts and crossover options provides you with the ability to adapt Westbury® railing to your needs. Optional post caps finished off by the convenience of a 2-piece post flair creates a variety of looks.

Posts




*Testing Results - CCRR-0163 complies with IBC[†], IRC[‡], and FBC. Note: Please check with local code authorities for requirements.









Wall & Angle Swivel Mounts





Stair Mounts





Stair Swivel Mounts





Double Swivel Stair Mount









Stair Crossover Post±



Level Crossover Post±



2", 2-1/2", 3", 4" & 6" Post Flair (2-piece)




Rail Support



Welded Corner







Ball Cap (2", 2-1/2", 4")

±Patent No. 8,998,175



Magena Star Ornamental Lights (Low Voltage)











